



## Proportional Valve with Control Electronics

- Control valve for continuous control of liquids
- Low hysteresis and high repeatability
- Control with PWM signal
- Servo-assisted, tight closing valve

Type 6223 can be combined with...



**Type 8605**

Control electronics  
Cable plug version



**Type 8605**

Digital control electronics  
DIN-rail version



**Type 2508**

Cable plug



**Type 8611**


Universal controller

The valve, Type 6223, can be used to control the flow of large amounts of liquids. Low hysteresis, high repeatability and good response sensitivity guarantee good positioning behaviour. The valve closes tight. The push-over coil is easy to replace.

Technical data	
<b>Orifice</b>	DN 10, 13 and 20 mm
<b>Body material</b>	Brass, stainless steel on request
<b>Seal material</b>	FKM, others on request
<b>Media</b>	Neutral liquids
<b>Media temperature</b>	-10 to + 90 °C
<b>Ambient temperature</b>	Max. + 55 °C
<b>Port connection</b>	G 3/8, G 1/2, G 3/4, G 1
<b>Viscosity</b>	Max. 21 mm <sup>2</sup> /s
<b>Operating voltage</b>	24 V DC
<b>Power consumption</b>	See ordering chart
<b>Duty cycle</b>	Continuous rating 100%
<b>Electrical connection</b>	Cable plug Type 2508 acc. to DIN EN 175301-803 Form A
<b>Protection class valve</b>	IP 65 with plug-on module or with cable plug on the valve
<b>Installation</b>	As required, preferably with actuator in upright position
<b>Hysteresis</b>	< 5%
<b>Repeatability</b>	< 1% FS
<b>Sensitivity</b>	< 1% FS
<b>Settling time (90%)</b>	< 200 ms
<b>Span</b>	1:10

## Ordering chart for valves (other versions on request)

### All valves with FKM sealing

Circuit function	Port connection	Orifice [mm]	Kvs value water [m <sup>3</sup> /h] <sup>1)</sup>	Q <sub>Nn</sub> value [l/min] <sup>2)</sup>	Pressure range [bar] <sup>3)</sup>	Max. coil current [mA]	Power consumption [W]	Item no.
 <p>2-way servo-assisted continuous control valve NC</p>	G 3/8	10	1.4	1510	0.5-10	300	8	134 229
	G 1/2		1.4	1510	0.5-10	300	8	134 230
	G 1/2	13	2.5	2700	0.5-10	330	10	132 202
	G 3/4		2.5	2700	0.5-10	330	10	132 640
	G 3/4		20	5.0	5400	0.5-10	530	15
	G 1	5.0		5400	0.5-10	530	15	222 477

1) Kvs value: Flow rate value for water, measured at +20 °C and 1 bar pressure differential over a fully opened valve

2) Q<sub>Nn</sub> value: Flow rate value for air with inlet pressure of 6 bar<sup>1)</sup>, 1 bar pressure differential and +20 °C

3) Pressure data [bar]: Overpressure with respect to atmospheric pressure; if the differential pressure over the valve exceeds 5 bar the characteristics may change.

**Please note** that the valves are delivered without control electronics unit and cable plug (see accessories below).

### **i** Further versions on request



#### Approvals

UR, CSA, CGA/AGA

## Ordering chart for accessories

### Cable plug Type 2508 according to DIN EN 175301-803 Form A

The delivery of a cable plug includes the flat seal and fixing screw

Circuitry	Voltage / frequency	Item no.
None	0 - 250 V AC/DC	008 376
None, with 3 m cable	0 - 250 V AC/DC	783 573

**Electronic Control Type 8605** - please see separate datasheet

## Dimensions [mm]

